



CONSTRUCTION

Conductor Annealed stranded copper rope

Application As earthing conductor

Packing coil, drum

Product number	Cross-section of conductors / number of strands x diameter mm ² / n x Ø mm	Outer diameter Ø mm	Max. resistance of conductor at + 20 °C Ω / km	Total weight kg / km	Standard packing m
	HK 6 / 7x1.05	3.3	3.080	53	drum
	HK 10 / 7x1.34	4.1	1.830	87	drum
0109005	HK 16 / 7x1.70	5.3	1.150	142	25 coil
0109006	HK 16 / 7x1.70	5.3	1.150	142	50 coil
0109007	HK 16 / 7x1.70	5.3	1.150	142	100 coil/5400 pallet
0109008	HK 16 / 7x1.70	5.3	1.150	142	drum
0109009	HK 25 / 7x2.15	6.6	0.727	224	drum
0109011	HK 50 / 19x1.78	9.2	0.387	421	drum
0109012	HK 70 / 19x2.15	11.0	0.268	615	drum
0109013	HK 95 / 19x2.50	12.3	0.193	787	drum
0109014	HK 120 / 37x2.01	14.3	0.153	1042	drum
0109015	HK 150 / 37x2.26	16.4	0.124	1336	drum